



# NIAGARA DEIONIZER

Niagara Deionizer, 110-115 VAC Light	<b>BA-MS-341</b>
Niagara Deionizer, 220-240 VAC Light	<b>BA-MS-342</b>
Niagara Replacement Cartridge	<b>BA-221</b>

### Disposable Cartridge

Removes 76,000 total dissolved solids (PPM) before needing replacement

Input TDS	Gal. Yield
100	760
150	507
200	380
250	304
300	253

### Water Quality Light

Green okay, red replace cartridge

### Low Pressure Bypass

Maintains pressure in the event a cartridge is not changed and becomes clogged

### 10 Foot Hose

Connects to spigot

### 20 Foot Supply Hose

With inline strainer

### Pressure Regulator

With flow indicator and quick coupler

Maximizes battery life by removing ions and heavy metals that are present in tap water. The separate bed deionizer uses an ion exchange cartridge to filter the water before it enters the battery. Cartridge can be discarded when replacement is necessary. This is determined when output exceeds 50 TDS (water quality light will turn red). The low pressure bypass ensures that the deionizer will provide enough pressure and flow to operate your SPW system, even if you forget to change out an old cartridge.

For batteries equipped with Millennium Plus+ or Pro-Fill systems (SPW system must have BA-QDV-500 or BA-QDV-505 Quick coupler.)

**1 FLOW-RITE CONTROLS  
1 YEAR WARRANTY**



Flow-Rite Controls, 960 74th St, Byron Center, MI 49315  
phone: 616-583-1700 ~ fax: 616-878-5151 ~ [www.flow-rite.com](http://www.flow-rite.com)

